

This document downloaded from  
**vulcanhammer.net**

since 1997,  
your source for engineering information  
for the deep foundation and marine  
construction industries, and the historical  
site for Vulcan Iron Works Inc.

Use subject to the “fine print” to the  
right.

Don't forget to visit our companion site <http://www.vulcanhammer.org>

All of the information, data and computer software ("information") presented on this web site is for general information only. While every effort will be made to insure its accuracy, this information should not be used or relied on for any specific application without independent, competent professional examination and verification of its accuracy, suitability and applicability by a licensed professional. Anyone making use of this information does so at his or her own risk and assumes any and all liability resulting from such use. The entire risk as to quality or usability of the information contained within is with the reader. In no event will this web page or webmaster be held liable, nor does this web page or its webmaster provide insurance against liability, for any damages including lost profits, lost savings or any other incidental or consequential damages arising from the use or inability to use the information contained within.

This site is not an official site of Prentice-Hall, the University of Tennessee at Chattanooga, Vulcan Foundation Equipment or Vulcan Iron Works Inc. (Tennessee Corporation). All references to sources of equipment, parts, service or repairs do not constitute an endorsement.


# ENCE 361 Soil Mechanics




Compaction of Soil:  
Earthwork Quantity  
Calculations

# Fill and Grade Work


"Let every valley be lifted up, and every mountain and hill be made low; and let the rough ground become a plain, and the rugged terrain a broad valley; Then the glory of the LORD will be revealed, and all flesh will see {it} together; for the mouth of the LORD has spoken." (Isa 40:4-5 NAS)



# Cut and Fill



GRAVEL	SAND	SILT	CLAY
--------	------	------	------



# Methods of Compaction and Soil Improvement

# Earthwork Quantity Example

## ☞ Cut area

### ☞ Result of soil sampling in cut area

- ☞ Twelve undisturbed soil samples taken
- ☞ Average dry unit weight of soil = 108 pcf
- ☞ Average water content = 9.1%

### ☞ Result of compaction tests on relative bulk sample

- ☞ Maximum dry unit weight @ 100% compaction = 124 pcf
- ☞ Water content at maximum dry unit weight = 12.8%
- ☞ Specifications call for at least 90% compaction
  - ☞ Will use 92% compaction for calculation

# Earthwork Quantity Example

## ☞ Grading plan

- ☞ 12,000 cu. yd. Of Cut
- ☞ 11,500 cu. yd. Of Fill

## ☞ Find

- ☞ Shrinkage factor
- ☞ Required volume of soils to either add or subtract from fill requirement to “make the cut”
- ☞ Compute weight of import or export in tons
- ☞ Compute the additional water (over what comes from the cut) to bring the fill to the optimum moisture content

# Earthwork Quantity Example

- What are we moving from one place to another?
  - Soil
  - Water
- Need to compute the following quantities first
  - Dry and wet unit weight of cut and fill
  - Soil weight in the cut specifications
  - Soil weight in the fill specifications

# Earthwork Quantity Example

## ☞ Dry and Wet Unit Weight

### ☞ Cut

☞ Dry =  $\gamma_1 = 108$  pcf (given)

☞ Wet =  $\gamma_3 = 108 (1+.091) = 117.83$  pcf

### ☞ Fill

☞ Dry =  $\gamma_4 = (124 \text{ pcf})C_r = (124)(0.92) = 114.08$  pcf

☞ Wet =  $\gamma_2 = 114.08 (1+.128) = 128.68$  pcf

# Earthwork Quantity Example

## ☞ Compute Soil Weights from Dry Unit Weights

### ☞ Cut

$$\begin{aligned} \text{☞ } W_{sc} &= V_{sc} \gamma_1 = (12,000)(27)(108) = 34,992,000 \text{ lbs.} = \\ &17,496 \text{ tons} \end{aligned}$$

### ☞ Fill

$$\begin{aligned} \text{☞ } W_{sf} &= V_{sf} \gamma_1 = (11,500)(27)(114.08) = 35,421,840 \text{ lbs.} = \\ &17,711 \text{ tons} \end{aligned}$$

☞ Amount of additional soil needed from cut to make fill specification =  $17,711 - 17,496 = 215$  tons

☞ Volume of soil based on cut dry unit weight =  $(429,840 \text{ lbs})/108 = 3980 \text{ ft}^3 = 147.41 \text{ yd}^3$

# Earthwork Quantity Example

☞ Compute total weight of cut moved (with water)

$$\begin{aligned}\text{☞ } W_{\text{additional total}} &= (3980 \text{ ft}^3)(117.83 \text{ pcf}) = 468963.4 \text{ lbs} \\ &= 234.5 \text{ tons}\end{aligned}$$

☞ Compute total water from original cut specification

$$\begin{aligned}\text{☞ } W_{\text{wc}} &= w_c W_{\text{sc}} = (0.091)(34,992,000 \text{ lbs.}) = \\ &= 3,184,272 \text{ lbs.} = 1592.14 \text{ ton}\end{aligned}$$

# Earthwork Quantity Example

☞ Compute total water from original fill specification

$$\text{☞ } W_{wc} = w_c W_{sc} = (0.128)(35,421,840 \text{ lbs.}) = 4,533,996 \text{ lbs.} = 2267 \text{ tons}$$

☞ Compute total water needed

$$\text{☞ } \Delta W = 2267 - 1592.14 = 674.86 \text{ tons}$$

☞ Compute water from additional cut material

$$\text{☞ } W_{add} = (215)(0.091) = 19.56 \text{ tons}$$

# Earthwork Quantity Example

☞ Compute weight of water that must be added directly to fill

$$\text{☞ } W_{\text{direct}} = 674.86 \text{ tons} - 19.56 \text{ tons} = 655.3 \text{ tons}$$

☞ Compute volume of water in gallons

$$\text{☞ } V_{\text{direct}} = (1728)(2000)(655.3)/((231)(62.4) = 157,116 \text{ gal.}$$

# Shrinkage Factor

☞ Shrinkage Factor

$$SF = \frac{\Delta V}{V} = \left( \frac{\gamma_{d_f}}{\gamma_{d_c}} - 1 \right) \times 100 \text{ percent}$$

☞  $SF = (114.08/108 - 1) \times 100 = 5.63\%$

# Questions

